ArchiTECH®

AB-800

110W 8" Down-Firing Subwoofer

Lossless Wireless Receiver Built-In

Features:

- The AB-800 Powered Subwoofer utilizes patented amplifier technology and careful driver and system design. The result is an affordable, high-performance wireless subwoofer that delivers true, deep bass to any system, and is modest in size.

- The AB-800 subwoofer and matching AB-TX transmitter fulfill the wish list of music enthusiasts everywhere:

  - Extra-long-throw, heavy-duty driver
  - Laboratory-tuned for true, deep-bass performance (-3dB@27Hz)
  - Automatic International Voltage

  - Wireless reception of music signal
  - Modest size hides in any room
  - Lossless, 2.4 gHz Frequency-Stepping Wireless Technology

- We've perfected even the smallest aspects of the AB-800: extra-large flared port to eliminate audible turbulence, non-reflective matte black polyvinyl finish to eliminate reflections during home theater presentations & 4 adjustable rubber feet that provide an acoustically isolated stable platform for optimal output. The AB-800 performs at levels previously unachieved!

5 YEAR PARTS & LABOR Limited Warranty

Dimensions:

- 13" W x 13" H x 13" D (330 W x 330 H x 330 D) mm (without feet)

AB-Tx - Lossless Wireless Transmitter

The AB-800 and AB-Tx Transmitter are the perfect combination to wirelessly add deep bass realism, in an affordable package that can easily fit into any room.

- Lossless digital signal
- 2.4 gHz

- 4-1/2" x 1-1/4" x 4-1/16"
- Sold separately

8" EXTRA LONG–THROW Heavy Duty Driver
Lossless Wireless Subwoofer

CEDIA® | RoHS conform | Rev. C

View all our ArchiTech Models:

ArchiTech®

OEM SYSTEMS
COMPANY INC.

AB-800
110W Powered Wireless Subwoofer

SERIAL NUMBER

110 Watt RMS BASH® Amplifier

Specifications

Frequency Response: 27Hz – 200Hz ± 3dB

Crossover Frequency: 50Hz – 200Hz variable (with bypass position)

Phase Adjustment: 0 – 180 degrees (selectable)

Amplifier Output Power: 110 watts, with thermal and clipping limiters

Audio Inputs: Summing stereo line level (RCA x2) or LFE Input

Input Impedance: Line level – 20k ohms, unbalanced

Input Power: 115 - 230V / 50-60Hz AC (auto-adjusting)

Input Power Connection: IEC C8 2-wire receptacle

Power Modes: Auto signal sensing, always on and standby

Auto Off Delay: ~10 minutes

Weight: 22 lbs (10 kg)

Dimensions: 13" W x 13" H x 13" D, (330 W x 330 H x 330 D)mm

Shipping Dimensions: 17" W x 17" H x 17" D, (431 W x 431 H x 431 D)mm

Shipping Weight: 26 lbs (11.8 kg)

5 YEAR PARTS & LABOR Limited Warranty

Included Hardware

Knurled Jam Nuts (4)

Rubber Feet (4)

*The **AB-800** and **AB-Tx** Wireless Transmitter are the perfect combination to add deep bass realism, in an affordable package that can easily fit into any room. Real bass thrills are no longer out of the reach of everyman!*