

Presence[®]

Valueline

HOME THEATER LOUDSPEAKERS

Welcome Home



PV-8LCRS

8" 2-way round **15° Angled Loudspeaker**
Poly woofers with butyl surround
Pivoting dome tweeter
Frequency response: 35 Hz - 20 kHz \pm 4 dB
Power handling: 60 watts nom. 120 max.
Sensitivity: 91dB 1 watt / 1 meter
Impedance: 8 ohm nominal
Overall dimension: 12-7/8" round
Cut-out: 11-1/2" round x 5-3/4" deep
Pre-construction bracket: **RIR-815**

The 15 degree angle enables significantly enhanced cinematic sound imaging when room layouts dictate ceiling mounted loudspeakers



PV-6LCRS

6-1/2" 2-way round **15° Angled Loudspeaker**
Poly woofers with butyl surround
Pivoting dome tweeter
Frequency response: 45 Hz - 20kHz \pm 4 dB
Power handling: 50 watts nom. 100 max.
Sensitivity: 91dB 1 watt / 1 meter
Impedance: 8 ohm nominal
Overall dimension: 10-3/4" round
Cut-out: 9-1/4" round x 5" deep
Pre-construction bracket: **RIR-615**



Magnetically Shielded
Orient vertically or horizontally

PV-LCRS

Dual 5-1/4" 2-way rectangular MTM
CENTER / ALL CHANNEL - LCRS
Poly woofers with butyl surround
Silk soft dome pivoting tweeter
Frequency response: 45 Hz - 20 kHz \pm 4 dB
Power handling: 50 watts nom. 100 max.
Sensitivity: 91dB 1 watt / 1 meter
Impedance: 8 ohm nominal
Overall dimensions: 9" x 15-3/4"
Cut-out: 7-7/8" x 14-7/16" x 3-1/2" deep
Pre-construction bracket: **RIB-LCR**

Lifetime Limited Warranty



OEM SYSTEMS COMPANY, INC.

(775) 355-0405 ♦ (775) 355-0646 FAX

www.presenceloudspeakers.com ♦ info@presenceloudspeakers.com

Product materials & specifications are subject to change / improvement