

Presence®

LOUDSPEAKERS FOR TODAY'S ARCHITECTURE



A-525

Dual 5-1/4" In-Wall
2-way Loudspeaker

A-650

6-1/2" In-Wall
2-way Loudspeaker

A-820

8" In-Wall
2-way Loudspeaker

A-830


8" In-Wall
3-way Loudspeaker

	A-525	A-650	A-820	A-830	
Woven Kevlar® Woofer with Butyl Rubber Surround	5-1/4"	6-1/2"	8"	8" 3-way	Woofer Size
Silk, Soft-Dome, Pivoting Tweeter	1"	1"	1"	3/4"	
1-3/8" Textile Soft Dome Midrange				✓	
Frequency Response	50 - 20K	45 - 20K	35 - 20K	35 - 20K	Hz ± 3 dB
Power Handling	40 / 80	50 / 100	60 / 120	60 / 100	watts nom. / max.
Sensitivity	91	91	91	91	dB 1 watt / 1 meter
Impedance	8	8	8	8	ohms
Overall Dimensions	6-3/4" x 9-3/8"	9-1/16" x 12-3/4"	10-1/2" x 14-1/2"	10-1/2" x 14-1/2"	W x H
Cut-Out Dimensions	5-1/2" x 8-3/16"	8" x 11-3/4"	9" x 13"	9" x 13"	W x H
Loudspeaker Depth	2-3/8"	3-1/4"	3-1/4"	3-1/4"	D
IR Knockouts		✓	✓	✓	

Features:

- High-temperature Polyimide voice coils
- Phase plug pole piece extensions
- High-grade crossovers
- Polyswitch overdrive protection
- Industry leading superior clamp-ring mounting system
- Frame and Grille may be painted to match mounting surface
- Sold and Shipped in Pairs

Optional Pre-Construction Brackets:



Supplied with Grille, Baffle and Frame

Welcome Home



OEM SYSTEMS COMPANY
(775) 355-0405 ♦ (800) 291-0561 FAX
www.oemsystems.com ♦ info@oemsystems.com

View all our
Presence
Models:

