

# Presence®

LOUDSPEAKERS FOR TODAY'S ARCHITECTURE



## A-6LCRS

6-1/2" In-Ceiling Loudspeaker

6-1/2" 2-way 15° Angled Loudspeaker

Frequency Response: 45Hz - 20kHz ± 3 dB

Power Handling: 50 watts nom. 100 max.

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: 1" Silk, soft-dome, pivoting tweeter

Cut-out dimensions: 9-1/4" dia. x 5" deep

Overall dimensions: 10-3/4" dia.

*Sold and shipped individually*

## A-8LCRS

8" In-Ceiling Loudspeaker

8" 2-way 15° Angled Loudspeaker

Frequency Response: 35Hz - 20kHz ± 3 dB

Power Handling: 60 watts nom. 120 max.

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: 1" Silk, soft-dome, pivoting tweeter

Cut-out dimensions: 11-1/2" dia. x 5-3/4" deep

Overall dimensions: 12-7/8" dia.

*Sold and shipped individually*

### Features:

- Woven Kevlar® woofers with butyl rubber surrounds
- High-temperature Polyimide voice coils
- High-grade crossovers
- Polyswitch overdrive protection
- Proven mounting system
- Frame and Grille may be painted to match mounting surface



Optional Pre-Construction Brackets



Supplied with grille, baffle & frame

*Welcome Home*



**OEM SYSTEMS COMPANY**  
(775) 355-0405 ♦ (800) 291-0561 FAX  
www.oemsystems.com ♦ info@oemsystems.com

View all our  
Presence  
Models:

