

Presence®

LOUDSPEAKERS FOR TODAY'S ARCHITECTURE



A-LCRS Dual 5-1/4" In-Wall Center Channel Loudspeaker

Frequency Response: 45Hz - 20kHz \pm 3 dB

Power Handling: 50 watts nom. 100 max.

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: 1" Silk, soft-dome, pivoting tweeter

Cut-out Dimensions: 7-7/8" x 14-7/16" x 3-1/2" deep

Overall Dimensions: 9" x 15-3/4"

Sold and shipped individually

Features:

- Woven Kevlar® woofers with butyl rubber surrounds
- High-temperature Polyimide voice coils
- Phase plug pole piece extensions
- IR Knockouts
- High-grade crossovers
- Polyswitch overdrive protection
- Industry leading superior clamp-ring mounting system
- Magnetically shielded
- Orient Vertically or Horizontally
- Frame and Grille may be painted to match mounting surface



optional pre-construction bracket:
RIB-LCR

Supplied with Grille, Baffle and Frame



Welcome Home



OEM SYSTEMS COMPANY
(775) 355-0405 ♦ (800) 291-0561 FAX
www.oemsystems.com ♦ info@oemsystems.com

View all our
Presence
Models:

