

Presence®

LOUDSPEAKERS FOR TODAY'S ARCHITECTURE



A-SP6

6-1/2" In-Ceiling Loudspeaker

6-1/2" 2-way Single Point Stereo Loudspeaker

Frequency Response: 45Hz - 20kHz ± 3 dB

Power Handling: 50 watts nom. 100 max.
both channels combined

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: Dual (L & R) 3/4" Silk, soft-dome tweeters

Cut-out dimensions: 7-3/4" dia. x 2-7/8" deep

Overall dimensions: 8-3/8" dia.

Sold and shipped individually

A-SP8

8" In-Ceiling Loudspeaker

8" 2-way Single Point Stereo Loudspeaker

Frequency Response: 35Hz - 20kHz ± 3 dB

Power Handling: 60 watts nom. 120 max.
both channels combined

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: Dual (L & R) 3/4" Silk, soft-dome tweeters

Cut-out dimensions: 8-5/8" dia. x 3-3/8" deep

Overall dimensions: 9-3/4" dia.

Sold and shipped individually

Features:

- Woven Kevlar® woofers with butyl rubber surrounds
- High-temperature Polyimide voice coils
- High-grade crossovers
- Polyswitch overdrive protection
- Proven Mounting System
- Frame and Grille may be painted to match mounting surface

Optional Pre-Construction Brackets



Supplied with grille, baffle & frame

Welcome Home



OEM SYSTEMS COMPANY
(775) 355-0405 ♦ (800) 291-0561 FAX
www.oemsystems.com ♦ info@oemsystems.com

View all our
Presence
Models:

