

Sound Terrain[®]

RS-8G

8" High Performance Rock Speaker
with Single or Dual Channel Input

Available in:

Granite Gray
RS-8G



Specifications:

Woofer:	8" Polypropylene w/ butyl rubber surround
Tweeter:	1" Soft Dome
Crossover:	Dual-Band Multi-Order Topology
Impedance:	8 ohms nominal
Baffle / Grille:	Sloped Front Baffle with Textured Aluminum Grille
Power Handling:	100W RMS, 200W Maximum
Sensitivity:	88dB 1W/1M
Frequency Response:	65Hz - 20kHz
Weight:	Sold and Shipped Individually - 23 lbs. /each
Dimensions:	17"W x 12"H x 12"D

The RS-8 Rock speaker is the most versatile rock speaker on the market. It readily handles three different connection and application formats;

- 1.) Solution 1: **Single Channel** operation requires two speakers for stereo reproduction (one for left channel and one for right).
- 2.) Solution 2: **Dual Channel** operation ONLY works with common ground amplifiers. DO NOT USE BRIDGE MODE AMPLIFIERS IN THIS CONFIGURATION OR DAMAGE MAY OCCUR TO THE AMPLIFIER. Most amplifiers are common ground. This operation requires only one speaker since both channels are combined within the speaker.
- 3.) Solution 3: **4X Single-Channel** operation can be used in multi-speaker installations without complex wiring or load-matching devices. This option provides a 32-ohm load for up to four RS-8 rocks connected in parallel to a single amplifier channel while maintaining an 8-ohm load. Amps with 4-ohm capability can drive up to eight rocks per amp channel. 25-volt commercial systems see a 20W load per speaker.



OEM SYSTEMS COMPANY

(775) 355-0405 • (800) 291-0561 FAX

www.oemsystems.com • info@oemsystems.com

