

Sound Terrain®

ST-6

6-1/2" High Performance In-Ground Landscape Speaker

Available in:

Garden Green



Security Brackets Included

Specifications:

Woofers:	6.5" Poly w/ butyl rubber surround
Tweeter:	3/4" Titanium dome
Crossover:	Dual-Band Multi-Order Topology
Impedance:	8 ohms nominal
Power Handling:	50W RMS, 100W maximum (8-ohm)
Sensitivity:	87dB 2.83V/1 M (1W)
Frequency Response:	70Hz - 20kHz
Shipping Weight:	14.5lbs (6.6kgs)
Net Weight:	10.5 lbs (4.8 kgs)
Selectable Tap Positions:	70V: 1, 2, 4, 8, 16, 32V / 100V: 2, 4, 8, 16, 32W
Mounting Depth:	12-3/4" (33cm) with bracket / 3"(7.6cm) w/o bracket
Dimensions:	13-7/8" (346mm) Dia. X 14-1/2" H (w/o brackets)



Selector Knob Detail

Get the Most Out of Your Outdoor Audio!

The **AW-IMP100WV-B** is a 100 watt outdoor surface-mount volume control with enclosure (flush-mount version also available - **AW-IMP100WV**). This Impedance-matching volume control can be configured to maintain a safe system load when multiple controls and speakers are connected. These controls utilize autoformers to efficiently transfer the power from amplifier to speaker. Ideal for use with outdoor landscape speakers.



The **RS-6** is a 6" 2-way High-Performance Single-Channel Rock Speaker with a weatherproof design



The **RS-62** is a 6" 2-way High-Performance Dual-Channel Rock Speaker with a weatherproof design



OEM SYSTEMS COMPANY

(775) 355-0405 • (800) 291-0561 FAX

www.oemsystems.com • info@oemsystems.com

